

FEED WAGONS



BUILT TOUGH FOR PERFORMANCE

www.sammachinery.co.nz



15m³ Tandem-axle, Chain Side-Feed



10m³ Tandem-axle, Chain Side-Feed



12m³ Tandem-axle, Belt Side-Feed

Ph 0508 726 726

SIDE AND CENTRE-FEED DELIVERY


FEATURES



BELT SIDE-FEED (OPTIONAL)
The PVC belt (2mm) with vulcanised cleats is standard on all belt side-feeds. The belt side-feed achieves an even flow of feed with excellent throw. Ideal for maize and palm kernel, providing a smooth and quiet operation.



CHAIN SIDE-FEED (OPTIONAL)
A popular option on SAM Feed Wagons - the 25mm conveyor bars provide a positive directional flow for a range of feeds. The heavy roller chains reduce maintenance requirements with the chain and sprocket design. All side-feeds are now stainless steel.



TRANS-TEX 22 DECK FLOOR
Standard on all SAM Feed Wagons Trans-Tex 22mm is a high-strength ply timber recognised for its high bending stiffness and high-impact resistance.



WEIGH SCALES AND DISPLAY (OPTIONAL EXTRA)
The Iconix FX15 display and load-cell system provides simple, accurate electronic weighing of feed quantities.

OVERVIEW

Known for practical design and easy to use operation, SAM Feed Wagons are developed from over 70 years' experience. Our range is built to perform in New Zealand's harsh farm environment regardless of where you are in the country.

Choose a SAM for:

- Shot blasted, primed and two-pot paint finish coated chassis
- High-tensile calibrated snig chains (10-13mm) used throughout
- Hydraulic sensor valve (controlling the floor/elevator speeds)
- Chain and sprocket drive-system - driven by hydraulic motors
- Load weigh scales can be fitted retrospectively

Our range of SAM Fertiliser Spreaders, Feed Wagons and Hydraulic Trailers are backed-up by a fast and comprehensive spare-parts support service from our Hamilton location.

Our team are also available for diagnostic support, as well as technical and sales information.

AVAILABLE MODELS

- **6m³ side-feed OR centre-feed delivery**
- **9m³ side-feed OR centre-feed delivery**
- **10m³ side-feed OR centre-feed delivery**
- **12m³ side-feed OR centre-feed delivery**
- **15m³ side-feed OR centre-feed delivery**

Both belt and chain side-feed conveyors are available.

OPTIONAL ACCESSORIES

- Electronic weigh scales and display indicator
- 400/60 x 15.5 14ply tyres (standard on 12 cubic metre)
- Remote tandem-axle greasing
- Hydraulic side-shift kit
- Chain side-feed conveyor
- Brakes (tandem-axle - front hubs)
- LED lights and safety flags

For more information chat with your local dealership, call us on 0508 726 726 or visit www.sammachinery.co.nz

SPECIFICATIONS

SIDE-FEED DELIVERY	9 CUBIC METRE	10 CUBIC METRE	12 CUBIC METRE	15 CUBIC METRE
AXLE TYPE	Tandem-axle 60 mm	Tandem-axle 60 mm	Tandem-axle 70 mm	Tandem-axle 70 mm
AXLE CAPACITY	8,000 kg	8,000 kg	12,000 kg	12,000 kg
WHEEL TYPE	11.5/80 X 15.3 12-ply	11.5/80 X 15.3 12-ply	400/60 x 15.5 14-ply	500/50 x 17 (14 ply)
JACK TYPE	70 mm screw jack	70 mm screw jack	70 mm screw jack	70 mm screw jack
OVERALL LENGTH	6.5 m	6.5 m	7.3 m	7.8 m
OVERALL WIDTH	2.5 m	2.5 m	2.5 m	2.6 m
INTERNAL BIN WIDTH	1.8 m	2.0 m	2.0 m	2.1 m
INTERNAL BIN HEIGHT	1.22 m	1.24 m	1.24 m	1.34 m
CAPACITY	9 m ³	10 m ³	12 m ³	15m ³
LOAD WEIGHT (GRASS SILAGE)	5.5 T	6 T	8 T	10 T
LOAD HEIGHT	2.35 m	2.35 m	2.35 m	2.6 m